

Product: | Doorguard reinforced door
Colours: | Natural Finish with Polyester Powder coats available

These days a traditional timber door just cannot provide the strength and security of its more robust steel counterpart. Likewise a traditional timber fire door has the same problems. The Pasiguard Doorguard range is among the strongest most durable of the doorsets available in the UK. Approved to BS 476: Part 22. Every PASIGUARD DOORGUARD doorset is custom made to suit the customer's individual requirements.



Doorsets are available either hollow or reinforced with a honeycomb centre, all doors are manufactured from superior quality steel in the frames. Standard doors are ambidextrous and can be handed on site, once handing has been agreed, strike and hinge Jamb's can be adjusted in length dependant on floor finishes allowing the frame to fit neatly into the preformed opening. All Doorguard doorsets come in primed finish as standard but can be finished to a range of RAL/BS colours.

A wide range of additional products are available to enhance the security of the doorset such as panic latches, panic bolts, deadlocks, door restraints, electronic locking, door closers, kick plates, threshold and seals, dogbolts, door viewers, louvers and Georgian wired glazed panels.

All Pasiguard installations are carried out by our trained operatives who undergo constant training to ensure that they provide as fast, efficient and trouble free fixing as possible. And come with an automatic 12 month fully inclusive warranty.

A range of fire rated steel doors are available, fully compliant to BS 476 Part 22, rated up to 4 hours.

A range of doors with LPS1175 security rating are also available.



Product: | Doorguard Steel reinforced door
Colours: | Natural Finish with Polyester Powder coats available

New to the Pasiguard range are the Doorguard MS Steel Door Sets. These Doors have been designed solely with security in mind. The specifications are as follows:



80 x 40 x 3mm RHS Box Section Outer Framework.

80 x 40 x 3mm Inner Frame with, 3 No. as above

Cross Section Support Beams.

3mm Thick H.R. Steel Face Plate

2 No. Chubb Dead Locks

3 No. Steel Hinge Bolts

3 No. Heavy Duty Purpose Made Hinges.



Quality Systems Certificate No 247
Assessed to ISO 9002



Certified to LPS 1056
LPCB Reference No 247v011
240 min Fireguard Roller Shutters
Assessed up to 7m sq



Certified to LPS 1197
LPCB Reference No 247x
For the maintenance and servicing
of Fireguard Roller Shutters

Disclaimer:

Our policy is one of continuous improvement and we reserve the right to alter any of the above details without prior notification.